



109 Kero Road, Carlstadt, NJ 07072  
 Tel: 718-599-5112 Fax: 718-387-7941  
 www.DoorStopNY.com

## Available Core Options



# PRODUCT DATA SHEET LAM-HPDL

## High Pressure Laminate Door

### SPECIFICATIONS

Maximum Size:	48" wide x 120" high, Pairs: 96" x 120" Larger doors (up to 60" x 144") for special use are also available. Call office for information.
Thickness:	1.375", 1.75", 2.0" and 2.25"
Core:	PC, SCL, 45, 90, 20
Veneers:	All major brands Pionite Formica, Nevamar, and Wilsonart
Stiles:	Matching Laminate Edgeband
Adhesives:	PVA meets or exceeds WDMA I.S. I-A for Type I flush wood door adhesive.
Lites:	Vision cut out & metal vision
Blocking:	Special blocking for hardware available upon request
Machining:	Bevel, hinge and lock, mortise lock, card lock, pivot and other hardware preps using state of the art CNC equipment.
Standards:	Meets WDMA I.S. I-A and AWI

#### Environmental / LEED Credit Contributions (Optional)

- MR 4: Recycled Content
- MR 5: Regional Materials
- MR 6: Rapidly Renewable Materials (Bamboo Veneer Only)
- MR 7: Certified Wood (FSC Pure, FSC % and FSC CW)
- IEQ 4.4: Low Emitting Materials / No Added Urea Formaldehyde