



109 Kero Road, Carlstadt, NJ 07072
 Tel: 718-599-5112 Fax: 718-387-7941
 www.doorstopny.com

PRODUCT DATA SHEET

FSCL-45: 45-Minute Fire-Resistant Door (5-Ply)

SPECIFICATIONS

Maximum Size: 48" wide x 120" high. Pairs 96" x 96"

Transoms: Call office for details.

Thickness: 1.75" only. 2.0" and 2.25" by special request.

Core: Structural Composite Lumber which complies with ANSIA208.1 up to 96" (Mineral core over 96")

Veneers: Many species of natural wood veneer are available. WDMA 'A' grade, book & running match are standard. Primed Hardboard, Primed MDF, MDO and Decorative Plastic Laminate are also available.

Stiles: 1.25" softwood stiles are standard. Matching hardwood stiles with LSL backer (used for rigidity) are also available. All dimensions prior to factory trimming and prefitting.

Rails: None.

Finish: TR-6 UV clear, custom stain to match color, or primed where applicable.

Adhesives: PVA meets or exceeds WDMA I.S.1-A for Type 1 flush wood door adhesive.

Lites: Metal vision frames with 1/4" glass (all types). Veneer wrapped metal visions by special request.

Blocking: Top rail, bottom rail, stiles, and special blocking for special hardware is available. Certain concealed hardware will require blocking & Mineral core construction.

Machining: Bevel, hinge and lock, mortise lock, cardlock, pivot and other hardware preps using state of the art CNC equipment.

Fire Rating: 45-Minute Intertek Testing Services / Warnock Hersey Listing. Neutral Pressure


Standards: Meets ANSI, WDMA I.S. 1-A and AWI

Environmental / LEED Credit Contributions (Optional)

MR 4: Recycled Content

MR 5: Regional Materials

IEQ 4.4: Low Emitting Materials / No Added Urea Formaldehyde



Intertek